

Vending Machine







ESPLUS TOUCH V8

A solution specifically designed to improve brand exposure and the shopping experience. Our ESPLUS TOUCH optimises the display of products by incorporating a large screen to replace the product window. An advanced concept to connect with your consumers and multiply your sales. A global solution adapted to all your audiences and capable of combining the most efficient technology with the most luxurious and elegant style on the market to guarantee a unique and unforgettable experience.



ANTI-VANDALISM PLATE CLOSURE



OPTIMIZATION, CAPACITY AND VOLUME



J-SUITE



ELEVATOR



ADVERTISING OPTIONS



PRODUCT OUTPUT DETECTION PHOTOCELLS



CUSTOMIZED SETUP TO SUIT YOUR REQUIREMENTS




TOUCHSCREEN DISPLAY

Main features A



MACHINE NAME	Unpacked MEASUREMENT	WEIGHT	CONSUMPTION	ELEVATOR	COOLING UNIT	KEYBOARD	PAYMENT METHOD
ESPLUS TOUCH V8	1835 x 802 x 1081	438kg	230V/100W	Yes	No	Touchscreen 43"	Bank card reader
ESPLUS TOUCH V8 R290	1835 x 802 x 1111	464kg	230V/440W	Yes	Yes	Touchscreen 43"	Bank card reader
ESPLUS TOUCH BLUETEC V8	1835 x 802 x 1081	438kg	230V/100W	Yes	No	Touchscreen 43"	Bank card reader
ESPLUS TOUCH BLUETEC V8 R290	1835 x 802 x 1111	464kg	230V/440W	Yes	Yes	Touchscreen 43"	Bank card reader





FEATURES

- Capacity up to 8 trays of up to 10 height-adjustable channels.
- · Temperature with or without cold group.
- Possibility to program the temperature and have an interior temperature of 4°C to 25°C.
- Operation in environments with 65% maximum humidity.
- Multi-sales system, capable of delivering several products in a single manoeuvre.
- 43" touch screen, which allows you to display products and buy through it.
- Detection of correct sales by means of photocells.
- Continuous self-test of operation.
- Expiration date programming by selection number or channel. It inhibits the sale of these products.
- Flexible configuration. Easy to change the position of channels and partitions without tools.
- Intelligent or manual auto-adjustment of the push force for each channel, adapting to the characteristics of each product.
- Product elevator, which allows for smooth, shock-free dispensing and a backlit product collection drawer for perfect selling.
- FIFO (First in First out) system, which ensures continuous product renewal.

DESIGN

Our ESPLUS TOUCH V8 machines, thanks to their adjustable channel system, have the advantage of adapting to any type of product. In addition, they have cutting-edge technology and an elegant and innovative design, resulting in a machine with high capacity and great product control. In addition, incorporate a 43" screen that helps to visualize all your products and give a unique and special user experience.

- Elegant and robust design with up to 3 door finishes (white, black and bluetec) and with the option of customization with corporate branding.
- Suitable for environments with low lighting thanks to its LED lighting at the product collection door and touch screen.
- Furniture with injected insulating foam, which guarantees perfect cooling and lower energy consumption.



OPTIONS

Channel

- It can incorporate a cooling group.
- Up to 4 lift positions, depending on the height of the product.
- Maximum flexibility to extract any type of product, using pusher channels or paddle channels.
- Customized configuration of trays and channels, adjusted to the type of product to be dispensed.
- Customization of the machine with vinyls.

3 4 5 6 7 8 9 10

Internal heater kit, which maintains the interior temperature 35°C above the ambient temperature, always up to a maximum of 25°C.

PROGRAMMING

- View all accounting and machine status information remotely from J-Suite.
- Make product and price changes remotely from J-Suite.
- Upload product images and advertising videos remotely from J-Suite.
- Control up to 4 satellite machines.

CAPACITY DIAGRAM

- Collection and sending of machine status data to the controller device in order to inhibit the sale of expired products.
- Price programming from the sales menu, language change, extractor unions, advertising... from the screen itself.

640 mm **WIDE TRAYS** 57,5 mm minimum Tray 8 Tray 7 Tray 6 1.209 mm Tray 5 2.5 mm each divider (separator) Minimum height 135 mm Tray 4 Tray 3 CHANNEL DEPTH Tray 2 560 mm Tray 1

HEIGHT TABLE

Holes visible	Distance between trays	Product height pusher	Product height on pallet
8	135	94,5	76
10	162	121,5	103
12	189	148,5	130
14	216	175,5	157
16	243	202,5	184
18	270	229,5	211
20	297	256,5	238
22	324	283,5	265
24	351	310,5	292
26	378	337,5	319

Flexibility in tray between 1 to maximum of 10 motors.



TELEMETRY





Our Jofemar electronic system J-LINK offers a wide range of functionalities to all our machines. One of them is the ability to use J-SUITE, our comprehensive and unified solution for machine management that allows you full control of the machine from anywhere in the world.



ADVANTAGES

- Compatibility in all Jofemar machines, you can use J-SUITE on all our products.
- Total stock control.
- Remote control of machines from your computer, tablet, or mobile phone.
- Compatible with other payment systems.
- Option to have a closed circuit card reader.
- Compatible with non-Jofemar machines through standard protocols.
- Management of product images and waiting videos remotely.



COST CUTTING



REAL-TIME STOCK CONTROL



CUSTOMER SATISFACTION



AGILITY IN ACCOUNTING



OPERATIONS ENHANCEMENT



ADMINISTRATIVE OPTIMIZATION



ENHANCED INFORMATION SECURITY



Innovation technology

Reliability



Ctra. Marcilla km 2 31350 Peralta · Navarra · España

Tel. +34 948 75 12 12

Fax +34 948 75 04 20

nacional@jofemar.com

www.jofemar.com





100% Jofemar

Technology





