

# Vision

E-S Plus  
BLUETEC

Large  
product sale



The Vision E-S Plus module allows significantly increasing the number of channels and the overall storage capacity in the machine to vend almost any type of product (tools, large electronic devices,...). It features a soft delivery elevator and 8 trays of up to 10 channels. Optionally, a cooling unit can be fitted. Can be managed from master, Coffeemar or MSK machines.

**FEATURES**

- Temperature: with or without cooling unit.
- Capacity for 8 trays of up to 10 height adjustable channels.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1169 x 714 mm glass front door.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 w.
- Soft delivery elevator.

**STRUCTURE**

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

**CREDIT MANAGEMENT**

- Through the master machine, Vision or Coffeemar machines.
- Through the payment pod.

**PROGRAMMING**

- Through the master machine, Vision or Coffeemar machines.
- Through the payment pod.

**OPTIONS**

- Cooling unit can be fitted.
- Spiral channels in the upper trays.



|                  | ESPLUS REFRIGER V7           |
|------------------|------------------------------|
| Temperature      | With/Without cooling unit    |
| Maximum capacity | 8 trays of up to 10 channels |
| Elevator         | Yes                          |
| Size (mm)        | 1,830 x 803 x 970            |
| Weight           | 325 kg                       |
| Energy supply    | 230 V, 50 Hz*                |
| Cooling unit     | Optional                     |

\*Check for other voltages.



ENERGY CLASS  
REGULATION (EU)  
2019/2018



VANDAL-PROOF  
LOCK



OPTIMISED  
CAPACITY AND  
VOLUME



ENERGY-SAVING  
LED LIGHTING



EASYFLEX  
DELIVERY  
SYSTEM



PRODUCT  
DELIVERY  
DETECTION  
PHOTOCELLS



ELEVATOR



Ctra. Marcilla km 2  
31350 PERALTA. Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20  
[www.jofemar.com](http://www.jofemar.com)

