



casia
stock control system

VISION CASIA CG

30% more capacity than a standard machine. Features a refrigerated cabinet with different temperature areas offering an innovative way of selling different products in just one machine.



ENERGY CLASS
REGULATION (EU)
2019/2018

FEATURES

- Cooled.
- Capacity for 6 and 2 height-adjustable trays with up to 10 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1100 x 515 mm glass front door.
- Continuous performance self-testing.
- Flexible setup, and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

PROGRAMMING

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

OPTIONS

- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Modem installation and J-SUITE communication interface.
- Online operation with real-time control of users and deliveries.
- Management of up to two slave dispensing machine for higher capacity and number of selections.
- Privacy adhesive option



REMOTE
CONNECTION



USER
IDENTIFICATION



100 %
CONFIGURABLE



MODULARITY



EASYFLEX
DELIVERY
SYSTEM



PRODUCT DELIVERY
DETECTION
PHOTOCELLS

	EASYCOMBO V7
Temperature	Cooled
Maximum capacity	6 trays of up to 10 channels and 2 trays of up to 7 channels
Elevator	No
Size (mm)	1,830 x 803 x 970
Weight	297 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Yes
Product in sight	Yes / Privacy adhesive option

*Check for other voltages.



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

