



VISION CASIA CGE

La Vision Casia CGE features EasyFlex, an exclusive flexible extraction system, developed by Jofemar. It stands out for the optimised capacity and volume, and its bespoke cooling unit that controls evenly the temperature inside the vendor, that allows storing and selling different products.

**CARACTERÍSTICAS**

- Cooled
- Capacity for 8 height-adjustable trays with up to 7 channels each.
- FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting with on/off programming.
- 1462 x 473.5 mm glass front door.
- Continuous performance self-testing.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.
- Soft delivery elevator.

**STRUCTURE**

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

**PROGRAMMING**

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

**OPTIONS**

- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Modem installation and J-SUITE communication interface.
- Online operation with real-time control of users and deliveries.
- Management of up to two slave dispensing machine for higher capacity and number of selections.
- Privacy adhesive option.

	VISION CASIA CGE
Temperature	Cooled
Maximum capacity	8 trays of up to 7 channels
Elevator	Yes
Size (mm)	1,830 x 803 x 935
Weight	325 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Yes
Product in sight	Yes / Privacy adhesive option

\*Check for other voltages.



ENERGY CLASS  
REGULATION (EU)  
2019/2018



REMOTE  
CONNECTION



USER  
IDENTIFICATION



100 %  
CONFIGURABLE



MODULARITY



EASYFLEX  
DELIVERY  
SYSTEM



PRODUCT DELIVERY  
DETECTION  
PHOTOCELLS



ELEVATOR



Ctra. Marcilla km 2  
31350 PERALTA. Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20  
[www.jofemar.com](http://www.jofemar.com)

