



Casia  
stock control system

VISION CASIA GE

Vision Casia GE is the most appropriate solution to vend high ticket items and/or sensitive products and packages, as it features a soft delivery elevator that delivers at a waist-height point, with soft precise movements. Keeps the products at room temperature.

**CARACTERÍSTICAS**

- Room temperature.
- Capacity for up to 8 height-adjustable trays with up to 7 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1462 x 473.5 mm glass front door.
- Continuous performance self-testing.
- Flexible setup, and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

**STRUCTURE**

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

**PROGRAMMING**

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

**OPTIONS**

- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Modem installation and J-SUITE communication interface.
- Online operation with real-time control of users and deliveries.
- Management of up to two slave dispensing machine for higher capacity and number of selections.
- Privacy adhesive option.

	VISION CASIA GE
Temperature	Room temperature
Maximum capacity	8 trays of up to 7 channels
Elevator	Yes
Size (mm)	1,830 x 803 x 935
Weigh	296 kg
Energy supply	230 V, 50 Hz*
Cooling unit	No
Product in sight	Yes / Privacy adhesive option

\*Otras tensiones, consultar.



CONEXIÓN REMOTA



IDENTIFICACIÓN DE USUARIO



100 % CONFIGURABLE



MODULARIDAD



SISTEMA DE EXTRACCIÓN EASY FLEX



FOTOCÉLULAS DE DETECCIÓN DE SALIDA DEL PRODUCTO



ASCENSOR



Ctra. Marcilla km 2  
31350 PERALTA. Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20

[www.jofemarm vending.com](http://www.jofemarm vending.com)

