



Vision

Pago/Payment E-S Plus

B L U E T E C

Payment pod

The payment pod for Vision Bluetec Vending machines is the perfect solution to completely control satellite vending machines. Side detached master module to control up to a combination of 4 slave vendors type Vision E-S and/or Vision E-S Plus. This new type of multiproduct sale point installation uses up less space and offers a higher variety of products.

FEATURES

- Vending machine temperature control through the module.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.

COMPATIBILITY

- Satellite Vision E-S and Vision E-S Plus vendors.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with six anchor points.
- High-capacity cash box with lock.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

PROGRAMMING

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting hand terminal.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.
- Telemetry by GSM or GPRS modem using the Jofemar Vending Track software. Includes data accounting, sales, incidences, prices, programming options or SMS to mobile phones in case of sold out products.




OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Control of up to four tubes to return manual loading excess.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Up to four slave vending machine modules for higher capacity and number of selections.
- Receipt printer.
- 10.1" advertisement screen or product selection touchscreen.

	TAOS+ ESPLUS REFRIGER V7
Temperature	-----
Number of trays	8 (in machine)
Number of motors	10 (in machine)
Elevator	-----
Size (mm)	1,830 x 1.051 x 970
Weight	-----
Energy supply	230 V, 50 Hz*
Cooling unit	Optional (in machine)

*Check for other voltages.



ENERGY CLASS
REGULATION (EU)
2019/2018



VANDAL-PROOF
LOCK



BANKNOTE AND
COIN MECHANISM
PAYMENT SYSTEMS



EXPIRATION
PROGRAMMING



IMPROVED
DESIGN



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

