

1

TAOS

0

TAOS slim

basic touch 10 air







BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



TROS The best payment and control for your machines.

The TAOS system is the perfect solution to completely manage satellite vending machines. Features the most advanced payment systems to control up to a combination of 4 slave vendors.

This new concept allows the installation of a multi-product vending point that takes up less space and offers different payment systems. It has one of the widest ranges of payment modules on the market.

Our solution stands out for featuring a fast and intuitive system to streamline the purchasing system and improve the user experience through the implementation of interactive touch screens.

TAOS Air. Basic unit to simultaneously manage up to 4 satellite vending machines with a cashless credit cards reader.

TAOS Slim. The TAOS Slim is the most suitable control unit to simultaneously manage up to 4 satellite vending machines in locations with limited space. Being the narrowest module, it allows to implement an installation that occupies less space, without reducing the offer in payment systems.

TAOS Basic. The most suitable solution for the total control of satellite vending machines. It equips the most advanced payment systems to manage up to 4 dispensing units, so they can work autonomously.

TAOS Touch 10. Control unit with integrated payment systems based on customer needs and able to manage up to 4 dispensing units. It includes a 10.1" touch screen with capacitive keyboard and offers an interactive navigation system or product selection based on categories, among others.



TOUCH SCREEN



ADAPTABLE AND CUSTOMISABLE MANAGEMENT SOFTWARE



CAN BE CONFIGURED DEPENDING ON NEEDS



REMOTE CLOUD CONNECTION

FEATURES

- Control unit with integrated payment systems capable of managing up to a maximum of four dispensing units.
- Microwaves module control.
- Control of Casia Lockers.
- Vending machine temperature control through the module.
- Continuous performance self-testing.
- Security, both in payments and in the sale of products. TAOS feature vandal-proof locks and payment systems with the latest advances in anti-fraud systems. In addition, they incorporate programmable security systems that avoid the sale of products unfit for consumption, control the temperature and their expiry.
- Interactivity. Possibility of featuring 10,1 and 17" tuchscreens.

- Previous integration, and as an option, allows the use of customer loyalty cards.
- Management automation thanks to web telemetry. Optimum traceability of products and stocks.
- Reliability in data capture.

STRUCTURE

- Modular cabinet structure, treated against rust and corrosion.
- Vandal-proof security lock with six anchor points and metallic coin
- High-capacity cash box with lock.









FEATURES

 Includes a display for viewing prices and credit.

TAOS Air

STRUCTURE

- Vandal-proof security lock. • Dimensions and weights: 337 x 185 x
- 953 mm / 9.7 kg • Opening to built in an EVA standard
- size cashless card reader.

CREDIT MANAGEMENT

· Jofemar card and key reader or any card reader that works in MDB protocol.

PROGRAMMING

- Compatible with Jofemar EasyFlash handheld terminal for data injectionand data extraction.
- Compatible with Jofemar EasyFlash handheld terminal for data injectionand data extraction.
- Compatible with the latest telemetry systems for the integral management of the machine remotely.
- RS232 port with accounting data output.

FEATURES

· Includes a display for viewing prices and credit.

TAOS Slim

STRUCTURE

- Vandal-proof security lock with six anchor points and metallic coin entrance.
- Dimensions and weights: 1825x 171,5x936 mm / 101,64Kg.

CREDIT MANAGEMENT

- · Jofemar card and key reader or any card reader that works in MDB protocol.
- Equips Jofemar coin mechanism and bill reader.

PROGRAMMING

- · System of programming and visualization of accounting data integrated.
- Compatible with Jofemar EasyFlash handheld terminal for data injectio-
- nand data extraction. · Compatible with the latest telemetry systems for the integral manage-
- ment of the machine remotely. RS232 port with accounting data output.

OPTIONS

· ADA model available.

FEATURES

 Includes a display for viewing prices and credit.

TAOS Basic

STRUCTURE

- · Vandal-proof security lock with six anchor points and metallic coin entrance.
- · Dimensions and weights:: 1825x248x936 mm / 110,25Kg.

CREDIT MANAGEMENT

- Jofemar card and key reader or any card reader that works in MDB protocol.
- · Equips Jofemar coin mechanism and bill reader.

PROGRAMMING

 System of programming and visualization of accounting data integrated.

- Compatible with Jofemar EasyFlash handheld terminal for data injectionand data extraction
- · Compatible with the latest telemetry systems for the integral management of the machine remotely.
- RS232 port with accounting data output.

OPTIONS

- · ADA model available. Available in Metal and Bluetec
 - finishes.

- Tickets printer.

TAOS Touch10

FEATURES

- · Control unit with integrated payment systems capable of managing up to a maximum of four dispensing units.
- Interactive navigation. Product selec tion based on categories and multilanguage support.

STRUCTURE

- Vandal-proof coin return drawer, with controlled lighting and greater capacity.
- Interchangeable peripheral board system.
- · Dimensions and weights:
- 1825x248x936 mm / 112,98Kg. · Manufactured according to regulations ADA.

CREDIT MANAGEMENT

- Coin payment systems (separator + 4 autorechargeable Hoppers).
- · Banknote payment systems: BT11, NV11 or NV200..
- Possibility of incorporating different bank card readers.

PROGRAMMING

- Programming and accounting data visualization system integrated and accessible using the touch screen of the machine.
- · Compatible with the Jofemar EasyFlash handheld terminal for data loading
- Compatible with the latest telemetry systems for the integral management of the machine remotely.
- RS232 port with accounting data output.

OPTIONS

- · Available in Metal and Bluetec finishes.
- Tickets printer.



Technological Innovation

Reliability

100% Jofemar

Technology



Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20 **www.jofemarvending.com**



VE-CT143EN02 R02 202010

