



Vision

ComboPlus

B L U E T E C

Automated sale of
refrigerated products

Vision ComboPlus Bluetec is fitted with a soft delivery elevator, and features EasyFlex, an exclusive flexible extraction system **adaptable to virtually any product and packaging**, developed by Jofemar. It stands out for the optimised capacity and volume, and its bespoke cooling unit that controls evenly the temperature inside the vendor, that allows storing and selling soft drinks in cartons, chocolate, healthy food items and similar products.

FEATURES

- Cooled.
- Capacity for 8 height-adjustable trays with up to 7 channels each.
- FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting with on/off programming.
- 1462 x 473.5 mm glass front door.
- Continuous performance self-testing.
- Health timer: Automatic security system to prevent selling out-of-date products. Programmable expiration date by selection number or channel.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.
- Soft delivery elevator.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system that guarantees efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Card and banknote readers can be fitted.

PROGRAMMING

- General on site programming and display system for the data accounting, accessible from inside the machine.
- Compatible with the Jofemar EasyFlash handheld terminal for stock control and accounting.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Pop-up billboard advertisement on the elevator.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Management of up to two slave vending machine for higher capacity and number of selections.
- External microwave ovens detached column controlled by the master machine. Self-activated when a product has been dispensed from the master machine. Individually heating time programmed per selection.

	COMBOPLUS V7
Temperature	Cooled
Maximum capacity	8 trays of up to 7 channels
Elevator	Yes
Size (mm)	1,830 x 803 x 935
Weight	325 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Yes

*Check for other voltages.



ENERGY CLASS
REGULATION (EU)
2019/2018



VANDAL-PROOF
LOCK



ENERGY-SAVING
LED LIGHTING



BANKNOTE AND
COIN MECHANISM
PAYMENT SYSTEMS



EASYFLEX
DELIVERY
SYSTEM



HEALTH TIMER:
EXPIRATION
PROGRAMMING BY
TEMPERATURE



PRODUCT DELIVERY
DETECTION
PHOTOCELLS



ELEVATOR



EXPIRATION
PROGRAMMING



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

