



Vision

EasyCombo

Comprehensive
vending solutions

30% more capacity than a standard machine. Features a refrigerated cabinet with different temperature areas offering an innovative way of selling FMCG products in just one machine.

FEATURES

- Cooled.
- Capacity for 6 and 2 height-adjustable trays with up to 10 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1100 x 515 mm glass front door.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup, and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

PROGRAMMING

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Management of up to two slave vending machine for higher capacity and number of selections.
- External microwave ovens detached column controlled by the master machine. Its availability and heating times depend on the selections. Self-activated when a product has been dispensed from the master machine. Individually heating time programmed per selection.
- Spiral channels in the upper trays.

	EASYCOMBO V7
Temperature	Cooled
Maximum capacity	6 trays of up to 10 channels and 2 trays of up to 7 channels
Elevator	No
Size (mm)	1,830 x 803 x 970
Weight	297 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Yes

lower trays according to instruction manual
*Check for other voltages.



CLASIFICACION ENERGETICA (EU) 2019/2018



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



EASYFLEX DELIVERY SYSTEM



HEALTH TIMER: EXPIRATION PROGRAMMING BY TEMPERATURE



PRODUCT DELIVERY DETECTION PHOTOCELLS



EXPIRATION PROGRAMMING



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

