



**Jofemar**  
VENDING

# Coffeemar





COFFEEMAR G250D

COFFEEMAR G546D  
COFFEEMAR G546D Control Unit

COFFEEMAR XL 46 CTG



VANDAL-PROOF  
LOCK



OPTIMISED  
CAPACITY AND  
VOLUME



ENERGY-SAVING  
LED LIGHTING



BANKNOTE  
AND COIN  
MECHANISM  
PAYMENT  
SYSTEMS

# Coffeemar

## A break full of flavour

The Coffeemar range of hot beverages machines is the only one in the market with a pressure valve in the brewing unit to keep constant pressure during the brewing cycle. This allows extracting all the aroma and flavour of the coffee beans from the first to the last drop. Features an aluminium boiler and a motorised water distributor, eliminating most of the electrovalves, thus reducing the maintenance costs and making the operation easier.

### FEATURES

- Pressure valve in the brewing unit to keep constant pressure during the complete brewing cycle.
- Motorised water distributor without electrovalves.
- Aluminium boiler with resistor and capped probes, with no contact with the water (avoiding o-rings and calcium oxide formation).
- Two cup-dispenser models, depending on the cup diameter (65-67 mm or 67-69 mm).
- Model XL 46, 80 mm diameter cups, up to 350 ml capacity.
- Adjustable stir-stick dispenser, between 75 mm and 115 mm long.
- Self-cleaning of mixing bowls, product exit and grinder assembly: manual or automatic (programmable).
- Anti-steam sugar-adding system directly into the cup.
- Continuous temperature control of the water in the boiler.
- Braking system at collection drawer.
- Coffee bean grinder assembly (own module).
- Easy cleaning and maintenance of removable elements.

### Coffeemar Bluetec XL 46, Coffee to go:

- Double coffee brewing unit, being able to dispense from both units at the same time, obtaining a final cup of up to 14 grams of coffee, in 350ml of water, dispensed in less than 25 seconds, or it can be configured to dispense two types of coffee.
- Delivery of lids for the cups, with the possibility of preselection and surcharge in price.

### STRUCTURE

- Smudge-proof stainless steel finishing.
- Steel cabinet treated against corrosion and rust and vandal-proof lock with a crowbar-resistant door integrated into the structure.

### CREDIT MANAGEMENT

- MDB payment systems ready, JF8 coin mechanism, BT11 billreader, cashless systems Jlink, or other compatible systems.

### PROGRAMMING

- Onsite general programming using the machine keypad, by hand held terminal EasyFlahs or through PC computer.
- Data storage and stock control and accounting.

### OPTIONS

- Self-feeding water kit (one 25L tanks in the G250 model, up to 2 25L tanks in the G546 and XL 46 models).
- Coffeemar Bluetec G546, Control Unit fitted to be connected to a Vision ES or ES Plus Vending machine.
- Water filters: anti-scale or flavour.
- Customisable image.



Coffee, tea, chocolate...  
Hot beverages taste better in the  
Coffeemar range of machines. Enjoy  
the full flavour of a good coffee during your breaks.



	COFFEEMAR G250D	COFFEEMAR G546D	COFFEEMAR G546D CONTROL U.	COFFEEMAR XL 46 - CTG
Services	300	500	500	500
Canisters	5+grano	6+grano	6+grano	6+ 2grano
Selections+ preselection	18+3	18+3	18+3	18+2
Whippers	3	4	4	4
Dimensions	1.500 x 500 x 575 mm	1.825 x 600 x 575 mm	1.825 x 600 x 575 mm	1.825 x 755 x 560 mm
Weight	100 kg	140 kg	140 kg	170 kg
Mains water supply	3/4 GAS			
Energy supply	230 V, 50 Hz*			
Maximum power	1,100 watts			2.000 watts
Satellite vending machines	No	No	Yes	No

\*Check for other voltages.



MOTORIZED WATER  
DISTRIBUTOR  
WITHOUT  
ELECTROVALVES



EASY CLEANING  
AND MAINTENANCE  
OF REMOVABLE  
ELEMENTS



ALUMINIUM  
BOILER



PRESSURE  
VALVE IN THE  
BREWING UNIT



**Jofemar**  
VENDING

**Technological**  
Innovation

**Reliability**

**100% Jofemar**  
Technology

## Jofemar

Ctra. Marcilla km 2  
31350 PERALTA, Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20  
[www.jofemar.com](http://www.jofemar.com)



VE-CT37EN02 R03  
05/21

